

HILUCK Your Trusted Chinese EV Partner	Changan Kaicheng V919 2025 model, CATL 53kwh, short wheelbase, high roof, standard 2-seater	Changan Kaicheng V919 2025 model, CATL 53kwh, short wheelbase, high roof, elite 2-seater	Changan Kaicheng V919 2025 model, CATL 53kwh, long wheelbase, high roof, elite 2-seater	Changan Kaicheng V919 2025 model, CATL 53kwh, short-axle, high-top, smart, 2-seater	Changan Kaicheng V919 2025 model, CATL 88kwh, long wheelbase, high roof, elite 2-seater	Changan Kaicheng V919 2025 model, fast delivery cabin, CATL 88kwh, long wheelbase, high roof, smart, 2-seater	Changan Kaicheng V919 2025 Business Class CATL 88kwh Business Travel Edition Elite 7-seater	Changan Kaicheng V919 2025 Business Class CATL 88kwh Business Travel Edition Luxury 7-seater	Changan Kaicheng V919 2025 Glory Edition Guoxuan 41kwh Short Wheelbase Low Roof Elite 2-seater
	-	-	-	-	-	-	-	-	-

Basic parameters (● Standard ○ Optional - N/A)

Manufacturer	Changan Kaicheng	Changan Kaicheng	Changan Kaicheng	Changan Kaicheng	Changan Kaicheng	Changan Kaicheng	Changan Kaicheng	Changan Kaicheng	Changan Kaicheng
level	Light Commercial Vehicle	Light Commercial Vehicle	Light Commercial Vehicle	Light Commercial Vehicle	Light Commercial Vehicle	Light Commercial Vehicle	Light Commercial Vehicle	Light Commercial Vehicle	Light Commercial Vehicle
Energy type	Pure electric	Pure electric	Pure electric	Pure electric	Pure electric	Pure electric	Pure electric	Pure electric	Pure electric
Time to market	2025.06	2025.06	2025.06	2025.06	2025.06	2025.06	2025.06	2025.06	2025.06
CLTC pure electric range (km)	310	310	301	310	-	-	451	451	280
Battery fast charging time (hours)	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.55
Battery fast charge capacity range (%)	30-80	30-80	30-80	30-80	30-80	30-80	30-80	30-80	30-80
Maximum power (kW)	110	110	110	110	110	110	110	110	70
Maximum torque (N·m)	260	260	260	260	260	260	256	256	175
Body structure	truck	truck	truck	truck	truck	truck	bus	bus	truck
Motor (Ps)	150	150	150	150	150	150	150	150	95
Length*Width*Height(mm)	4995*1910*2380	4995*1910*2380	5495*1910*2380	4995*1910*2380	5495*1910*2370	5495*1910*2370	5495*1960*2370	5495*1960*2370	5015*1910*1990
Official 0-100km/h acceleration (s)	-	-	-	-	-	-	-	-	-
Maximum speed (km/h)	90	90	90	90	90	90	135	135	90
Curb mass (kg)	1850	1850	1900	1850	2240	2240	2470	2470	1740
Maximum full load mass (kg)	3495	3495	3495	3495	3510	3510	3320	3320	3200

body (● Standard ○ Optional - N/A)

Length (mm)	4995	4995	5495	4995	5495	5495	5495	5495	5015
Width (mm)	1910	1910	1910	1910	1910	1910	1960	1960	1910
Height (mm)	2380	2380	2380	2380	2370	2370	2370	2370	1990
Wheelbase (mm)	3150	3150	3500	3150	3500	3500	3500	3500	3150
Front wheelbase (mm)	1650	1650	1650	1650	1650	1650	1650	1650	1650
Rear track (mm)	1650	1650	1650	1650	1650	1650	1650	1650	1650
Approach angle (°)	26	26	26	26	25	25	25	25	25
Departure angle (°)	twenty two	twenty two	19	twenty two	18	18	18	18	twenty one
Body structure	truck	truck	truck	truck	truck	truck	bus	bus	truck
Door opening method	Casement door + sliding door	Casement door + sliding door	Casement door + sliding door	Casement door + sliding door	Casement door + sliding door	Casement door + sliding door	Casement door + sliding door	Casement door + sliding door	Casement door + sliding door
Number of doors	● 4	● 4	● 4	● 4	● 4	● 4	● 4	● 4	● 4
Number of seats	● 2 ○ 3	● 2 ○ 3	● 2 ○ 3	● 2 ○ 3	● 2 ○ 3	● 2 ○ 3	● 7 ○ 9	● 7 ○ 9	● 2 ○ 3
Trunk volume (L)	-	-	-	-	-	-	-	-	-
Cargo box size (mm)	2880x1740x1750	2880x1740x1750	3380x1740x1750	2880x1740x1750	3380x1740x1750	3380x1740x1750	-	-	2880x1740x1385
Drag coefficient (Cd)	-	-	-	-	-	-	-	-	-

electric motor (● Standard ○ Optional - N/A)

Rear motor model	TZ180XS133	TZ180XS133	TZ180XS133	TZ180XS133	TZ180XS133	TZ180XS133	TZ180XS133	TZ180XS133	TZ180XS018B	
Motor type	Permanent magnet/synchronous	Permanent magnet/synchronous	Permanent magnet/synchronous	Permanent magnet/synchronous	Permanent magnet/synchronous	Permanent magnet/synchronous	Permanent magnet/synchronous	Permanent magnet/synchronous	Permanent magnet/synchronous	Permanent magnet/synchronous
Total motor power (kW)	110	110	110	110	110	110	110	110	70	
Total motor horsepower (Ps)	150	150	150	150	150	150	150	150	95	
Total torque of the motor (N·m)	260	260	260	260	260	260	256	256	175	
Maximum power of rear motor (kW)	110	110	110	110	110	110	110	110	70	
Maximum torque of rear motor (N·m)	260	260	260	260	260	260	256	256	175	

Front seat functions	-	-	-	-	-	-	-	● Heating (driver's seat only) ● Ventilation (driver's seat only)	-
Electric seat memory function	-	-	-	-	-	-	-	-	-
Second row seat adjustment	-	-	-	-	-	-	● Backrest adjustment	● Backrest adjustment	-
Rear seat folding	-	-	-	-	-	-	-	-	-
Front/rear center armrest	-	-	-	-	-	-	-	-	-
Rear cup holder	-	-	-	-	-	-	-	-	-

Audio/Interior Lighting (● Standard ○ Optional - N/A)

Speaker brand name	-	-	-	-	-	-	-	-	-
Number of speakers	● 2 speakers	● 2 speakers	● 2 speakers	● 2 speakers	● 2 speakers	● 2 speakers	● 4 speakers	● 4 speakers	● 2 speakers
Interior ambient lighting	-	-	-	-	-	-	-	-	-

Air conditioning/refrigerator (● Standard ○ Optional - N/A)

Air conditioning temperature control method	● Manual air conditioning	● Manual air conditioning	● Manual air conditioning	● Manual air conditioning	● Manual air conditioning	● Manual air conditioning	● Automatic air conditioning	● Automatic air conditioning	● Manual air conditioning
Rear independent air conditioning	-	-	-	-	-	-	-	-	-
Rear seat air vents	-	-	-	-	-	-	-	-	-
Temperature zone control	-	-	-	-	-	-	-	-	-
Car air purifier	-	-	-	-	-	-	-	-	-
In-car PM2.5 filter	-	-	-	-	-	-	-	-	-